



Mentor Visual iQ+ Pratt and Whitney F100 Video Borescope kits

Waygate Technologies Video Borescope kits configured for Pratt and Whitney F100 series engines single-probe MViQ+ kit

Kit applicability

The compact, dual-probe kit contains a Waygate Technologies Touch model of the Mentor Visual IQ+ video borescopes and one 6.2mm x 3.5m probe with 1.4mm internal working channel.

The kit, with its included optical tip adapters and included accessories is configured to meet the P&W F100 engine borescope inspection tooling requirements. See the technical description summary on reverse side of this document for additional details.

Waygate Technologies offers no opinion and makes no conclusions as to whether these Waygate Technologies video borescopes meet the borescope inspection tooling requirements.

Kit part number

MVIQ6235AR-F100 (F100 kit with wi-fi radio)

MVIQ6235AN-F100 (F100 kit without wi-fi radio)





Technical description

Part number	MVIQ6235AR-F100	MVIQ6235AN-F100
Wifi and bluetooth radios	Included	Not included
Included standard accessories	Dual-probe capable wheeled shipping case containing, battery charger and power cord, optical tip case, 16GB USB thumb drive with user manual and an accessory pouch.	
6.2 mm probe	6.2 mm x 3.5 m Probe with 1.4 mm internal working channel	
Shipping box dimensions	22" wide x 13" deep x 25" tall	
System weight in case	42.5 lbs	
User interface	Menu-driven and soft button operation; menu navigation using either touchscreen or joystick	
Ergonomic design	Unitized hand-held design with interchangeable QuickChange probes	
Illumination	White LED	
Measurement	Real3D Stereo with point cloud visualization	
Articulation	360° All-Way® tip articulation, minimum of 130-degree deflection	
Internal memory	32 GB	
Zoom	5X continuous digital zoom	
Battery	2-hr Li ion battery pack, charge while attached or detached from handset	
Display	6.5" XGA LCD, daylight readable with touchscreen	
I/o ports	(2) USB 3.0 "A" port, (1) USB 3.0 client micro 'B' port	
Video output	DisplayPort digital video output	
Still image formats	Bitmap (.BMP) and JPEG (JPG)	
Video format	MPEG4 AVC/H.264 (.MP4 file)	
IP rating	IP65 (assembled), IP55 (disassembled)	
Additional accessories	6.2 mm x 3.5 mm probe working channel tool kit, with tools shown below, additional battery, handset mounting clamp, handset hanging hook, and 6", 12", and 16" rigid sleeves and gripper	
Military standard compliance	MIL-STD-810G 501.5, 502.5, 506.5, 507.5, 509.5, 510.5, 511.5, 514.6, 516.6, 521.3 MIL-STD-461G electromagnetic compatibility with RE102, and RS103 – above deck	
Agency compliance	Group 1 Class A; EN61326-1, IEC CB Scheme, UL/EN/CSA-C22.2 61010-1, IEC 62133, UN/DOT T1-T8, EU RoHS 2, EU RED Directive, ISTA 2G	

Optical tip set

Diameter	Part number	Optical viewing direction, DOF and tip color code	FOV (degrees)	DOF (mm)	DOF (inches)
6.2mm	T6280FF	Forward view, far DOF, silver ring	80	35 - inf	1.38- inf
6.2mm	T62120FN	Forward view, near DOF, black	120	2 - 200	0.08 - 7.87
6.2mm	T62120FF	Forward view, far DOF, yellow	120	15 - inf	0.59 - inf
6.2mm	T62120SN	Side view, near DOF, blue	120	6 - inf	0.24 - inf
6.2mm	T6280SF	Side view, far DOF, green	80	15 - inf	0.59 - inf
6.2mm	TM626060FN	Forward view, near DOF, black	60/60	2 - 200	0.08-7.87
6.2mm	TM626060SN	Side view, near DOF, blue	60/60	2 - 200	0.08-7.88

Working channel tools

Basket	Snare	Grasper	Hook
			
WT-304030B	WT-141432S	WT-141435P	WT-141435HC + WT-H